



Aitken Freeman P/L

Factory 7, 7-9 Brough St

Springvale Vic 3171

PO Box 548

Noble Park Vic 3174

Ph: 03 9701 3955

Fax: 03 9701 3956

Web: www.aitkenfreeman.com

email: sales@aitkenfreeman.com

Pavecure P

INTRODUCTION

Pavecure P is a high quality polymer emulsion for use in curing concrete, to reduce moisture loss from the surface due to evaporation.

BENEFITS

- Economical means of curing concrete
- Contains no wax - dries clear
- Single coat - easy application
- Water based material – safe and equipment can be washed in water
- Contains fugitive dye – so that you can easily see whether areas have been covered evenly

USES

Pavecure P is suitable for use on all freshly laid concrete either smooth or textured, indoors or outdoors. Pavecure P will help to reduce moisture loss due to evaporation from the surface of concrete.

SURFACE APPLICATION

Apply Pavecure P to the concrete as soon as the bleed water has gone and the new concrete has hardened sufficiently so as not to be marked by the application process. Apply Pavecure P undiluted at a rate of 1 litre per 5 m². Best applied by spray, however, may also be applied by brush, roller or broom.

SUPPLY & PACKAGING

Pavecure P is available in either 20 litre or 200 litre drums. Pavecure P should be stored in a cool, dry place in original unopened containers. Shelf life under these conditions is 12 months.

PRECAUTIONS

Pavecure P is designed for use in ambient temperatures between 5° - 40° C and all properties listed above assume a temperature of 20°C. Where conditions outside this range are encountered, please consult our technical staff prior to application.

Always read the product data sheet, MSDS and product label prior to use of this material.

TYPICAL PROPERTIES AND APPLICATION DATA

<i>Appearance:</i>	Milky	homogenous
	liquid	with green
	fugitive dye	
<i>Coverage:</i>	5m ² per litre	
<i>Dry Time:</i>	<i>Tack Free:</i>	1 - 3 hours
	<i>Hard Dry:</i>	4 - 8 hours
	<i>Trafficable:</i>	24 hours
<i>Application Temperature:</i>	10°C - 35°C	
<i>Application By:</i>	- Spray	- Brush
	- Roller	- Broom
<i>UN Number:</i>	Not applicable	
<i>Hazchem Code:</i>	Not applicable	
<i>Packaging Group:</i>	Not applicable	
<i>Poison Schedule:</i>	Not scheduled	
<i>Dangerous Goods Class:</i>	Not applicable	

TECHNICAL SUPPORT

Through our experienced sales team, Aitken Freeman can offer technical support to users and specifiers, and can arrange on-site visits to end users and contractors.

ALLIED PRODUCTS

Aitken Freeman P/L is an Australian company which manufactures and distributes a comprehensive range of high quality, high performance construction products including:

- Grouts and anchoring systems
- Epoxy Surface Coatings
- Admixtures for concrete
- Adhesives & Sealants
- Floor toppings
- Floor levelling compounds
- Concrete Repair materials
- Waterproofing solutions

Refer to Material Safety Data Sheet for precautions and personal protection prior to use of this product

Disclaimer: Any advice, recommendation, information, assistance or service provided by Aitken Freeman P/L in relation to goods manufactured or supplied by them or their use and application is in good faith and is believed by Aitken Freeman P/L to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Aitken Freeman P/L is provided without liability.