



Aitken Freeman P/L
Factory 7, 7-9 Brough St, Springvale Vic 3171
PO Box 548, Noble Park Vic 3174
Ph: 03 9701 3955 Fax: 03 9701 3956
Web: www.aitkenfreeman.com
email: sales@aitkenfreeman.com

Waterproofer No 2

Integral Water Resisting Admixture for Concrete & Masonry

USES

Waterproofer No 2 is an integral water resisting admixture for concrete and masonry, for use above and below ground. It is recommended for use wherever coloured mortar or integral floor colours are used.

BENEFITS

- Ready for use straight from container
- Water based formulation; easy clean up
- Economical material cost
- Improved workability and durability for concrete and masonry mixes
- Suitable for after trades

TYPICAL PROPERTIES

<i>Appearance</i>	Milky white liquid
<i>Specific Gravity @ 20°C</i>	0.98 gm/ml
<i>pH @ 20°C</i>	9.5 – 10.5

PREPARATION

All surfaces to be coated should be clean, sound and free from any contamination which would inhibit bond. Cracked or damaged concrete should be repaired or removed, and any oil, grease or chemical contamination must be removed prior to application of any mortar or render which contains Waterproofer No 2.

MIXING

Waterproofer No 2 is suitable for use as supplied straight from the container.

APPLICATION

Add the Waterproofer No 2 to the mix at the rate of one litre per 40kg of Portland cement. Add the Waterproofer No 2 to the gauge water rather than directly to the mix wherever possible. Do not premix with any other admixture, always add other admixtures separately to the mix.

CURING

Mortars and renders which have been modified with Waterproofer No 2 should be cured with an Aitken Freeman curing compound, such as Pavecure A or Pavecure W.

CLEAN UP

All equipment should be cleaned immediately after use with clean water.

SUPPLY

Waterproofer No 2 is available in 5 & 20 litre plastic drums, and 200 litre metal drums.

STORAGE

Waterproofer No 2 should be stored in a cool, dry place in original unopened containers. Shelf life under these conditions is 12 months.

PRECAUTIONS

Waterproofer No 2 is designed for use in ambient temperatures between 10° - 35° C and all properties listed above assume a temperature of 20°C. Where conditions outside this range are encountered, please consult our technical staff prior to application.

Material Safety Data Sheets (MSDS) are available to users of Aitken Freeman products on request. Please ensure you have read this data sheet, the MSDS, and the product label carefully before first use of any product.

TECHNICAL SUPPORT

Aitken Freeman offers a comprehensive range of high quality, high performance construction products. In addition, Aitken Freeman offers technical support to users and specifiers, and can arrange on-site visits to end users and contractors.

ALLIED PRODUCTS

Aitken Freeman manufactures a broad range of construction products and can supply the following:

- Grouts and anchoring systems
- Epoxy Surface Coatings
- Admixtures for concrete
- Adhesives & Sealants
- Floor toppings
- Floor levelling compounds
- Concrete Repair materials
- Waterproofing solutions

Refer to Material Safety Data Sheet for precautions and personal protection

Disclaimer: Any advice, recommendation, information, assistance or service provided by Aitken Freeman P/L in relation to goods manufactured or supplied by them or their use and application is in good faith and is believed by Aitken Freeman P/L to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Aitken Freeman P/L is provided without liability.