



**AITKEN FREEMAN**

Aitken Freeman P/L  
Factory 7, 7-9 Brough St  
Springvale Vic 3171  
PO Box 548  
Noble Park Vic 3174  
Ph: 03 9701 3955  
Fax: 03 9701 3956

Web: [www.aitkenfreeman.com](http://www.aitkenfreeman.com)  
email: [sales@aitkenfreeman.com](mailto:sales@aitkenfreeman.com)

# Sealcrete

## INTRODUCTION

Sealcrete is a cementitious, acrylic, decorative coating for masonry and concrete structures.

## BENEFITS

- Dries to a uniform finish
- Totally waterbased
- Two pack
- Environmentally friendly
- Can be applied by spray, roller or brush
- Will not yellow in sunlight
- Takes most after trades
- Equipment washable in water

## USES

Sealcrete is suitable for application to concrete as a protective or decorative coating. Applications include painting out graffiti and provision of a uniform and durable finish to structures such as bridges, columns and precast panels.

## SURFACE APPLICATION

The areas to be coated with Sealcrete must be clean, dry and free of oil, grease or other contaminants which may affect adhesion of the product. Loose concrete or other material should be removed from the surface and repaired prior to application of the Sealcrete.

Predampen the concrete to minimise premature drying of the coating.

Add the Powder to the Liquid component while mixing. Mix thoroughly for a further 3 minutes using a drill and suitable paddle.

Apply to the substrate using brush, roller or spray.

Apply within 40 mins. Do not retemper the mix after the initial set has taken place.

NOTE: Ensure all equipment is thoroughly cleaned in water.

## TYPICAL PROPERTIES AND APPLICATION DATA

<i>Appearance:</i>	Cement based coating
<i>Coverage:</i>	3 - 5m <sup>2</sup> per litre
<i>Flash Point:</i>	Not applicable
<i>Solvents:</i>	Not applicable
<i>Shelf Life:</i>	12 months maximum
<i>Dry Time: Tack Free:</i>	1 - 3 hours
<i>Application Temperature:</i>	10°C - 35°C
<i>Application By:</i>	- Spray - Brush - Roller
<i>Packaging:</i>	- 6.5 litre kits
<i>UN Number:</i>	Not applicable
<i>Hazchem Code:</i>	Not applicable
<i>Packaging Group:</i>	Not applicable
<i>Poison Schedule:</i>	Not applicable
<i>Dangerous Goods Class:</i>	Not applicable

## Precautions

Do not apply if rain is expected in the first 24 hours.

Do not thin with water or other liquids.

Always apply two (2) coats for a uniform finish.

### **Refer to Material Safety Data Sheet for precautions and personal protection**

**Disclaimer:** Any advice, recommendation, information, assistance or service provided by Aitken Freeman P/L in relation to goods manufactured or supplied by them or their use and application is in good faith and is believed by Aitken Freeman P/L to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Aitken Freeman P/L is provided without liability.