



AITKEN FREEMAN

Aitken Freeman Pty Ltd
Factory 7, 7-9 Brough St
Springvale Vic 3171
PO Box 548
Noble Park Vic 3174
Ph: 03 9701 3955
Fax: 03 9701 3956

Web: www.aitkenfreeman.com
email: sales@aitkenfreeman.com

Resiloc Thinners

Solvent for general purpose cleaning and thinning

DESCRIPTION

Resiloc Thinners is a solvent designed for general purpose clean up of equipment. Resiloc Thinners is not suitable for hardened epoxy products.

BENEFITS

- Good Cleaning Efficiency
- Economical material
- Dries to a oil free finish
- Single pack
- Compatible with most resin systems
- Easy application by spray, roller or brush

USES

Resiloc Thinners is suitable for most sealers and resin based compounds, including two pack systems before they harden.

MIXING

Resiloc Thinners is suitable for application straight from the container without prior mixing.

APPLICATION

Add the Resiloc Thinners to the product in accordance with the manufacturer's advice.

Applications for spraying may require up to 10% Thinners.

CLEAN UP

Resiloc Thinners may be used to clean up equipment immediately after use.

TYPICAL PROPERTIES AND APPLICATION DATA

<i>Appearance:</i>	Clear liquid
<i>Odour:</i>	Aromatic
<i>Solubility in Water:</i>	Insoluble
<i>Flash Point:</i>	38°C
<i>Shelf Life:</i>	12 months maximum
<i>Application Temperature:</i>	10°C - 35°C

SUPPLY

Resiloc Thinners is supplied in 20 litre or 200 litre drums.

STORAGE

Resiloc Thinners should be stored in a cool, dry place in original unopened containers. Shelf life under these conditions is 12 months.

PRECAUTIONS

Resiloc Thinners is designed for use in ambient temperatures between 10° - 35° C and all properties listed above assume a temperature of 20°C. Where conditions outside this range are encountered, please consult our technical staff prior to application.

Resiloc Thinners is a solvent based product, so protective goggles and clothing should be worn. Ventilation must be provided or self contained breathing apparatus may be appropriate.

Resiloc Thinners may affect some rubber and plastic components causing them to dissolve, swell or break down over time.

Do not store Resiloc Thinners or diluted products in plastic containers that are not compatible, or not suitable for solvent based products.

Check the suitability of using Resiloc Thinners prior to commencing the application.

Material Safety Data Sheets (MSDS) are available to users of Aitken Freeman products on request. Please ensure you have read this data sheet, the MSDS, and the product label carefully before first use of any product.

TECHNICAL SUPPORT

Aitken Freeman offers a comprehensive range of high quality, high performance construction products. In addition, Aitken Freeman offers technical support to users and specifiers, and can arrange on-site visits to end users and contractors.

ALLIED PRODUCTS

Aitken Freeman manufactures a broad range of construction products and can supply the following:

- Grouts and anchoring systems
- Epoxy Surface Coatings
- Admixtures for concrete
- Adhesives & Sealants
- Floor toppings
- Floor levelling compounds
- Concrete Repair materials
- Waterproofing solutions

Refer to Material Safety Data Sheet for precautions and personal protection

Disclaimer: Any advice, recommendation, information, assistance or service provided by Aitken Freeman Pty Ltd in relation to goods manufactured or supplied by them or their use and application is in good faith and is believed by Aitken Freeman Pty Ltd to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Aitken Freeman Pty Ltd is provided without liability.