



Aitken Freeman Pty Ltd  
Factory 7, 7-9 Brough St, Springvale Vic 3171  
PO Box 548, Noble Park Vic 3174  
Ph: 03 9701 3955 Fax: 03 9701 3956  
Web: [www.aitkenfreeman.com](http://www.aitkenfreeman.com)  
email: [sales@aitkenfreeman.com](mailto:sales@aitkenfreeman.com)

# Form Release Oil

## Release agent for steel and timber formwork

### USES

Form Release Oil is a light oil based release agent for formwork for concrete.

### BENEFITS

- Economical – good coverage
- Ease of application
- Improves concrete surface finish
- Ready to use from container

### DESCRIPTION

Form Release Oil is light oil based release agent that contains reactive components to ensure a clean and even concrete finish.

### TYPICAL PROPERTIES

Colour	Amber liquid, dries clear
Specific Gravity	< 1.0 gm/ml

### APPLICATION

#### Preparation

The areas to be treated with Form Release Oil must be free of oil, grease or other contaminants.

#### Priming

Priming is not required for this product.

#### Mixing

Form Release Oil is supplied ready to use from the container. Do not add solvent, diesel or other oils.

#### Installation

Spray application will ensure a light and even film of Form Release Oil. Apply two even coats to new timber formwork. Application should be several hours prior to pouring concrete. Rain affected formwork may need an additional coat.

### CLEAN UP

All spray equipment should be cleaned thoroughly before and after application to avoid contamination.

### SUPPLY

Form Release Oil is supplied in 20 litre steel drums. Coverage on sealed forms or steel will be 30m<sup>2</sup> per litre. New timber formwork will require a minimum of 2 coats at a coverage of 15 - 20m<sup>2</sup> per litre.

### STORAGE

Form Release Oil should be stored in a cool, dry place in original unopened containers. Shelf life under these conditions is 12 months.

### PRECAUTIONS

Form Release Oil is designed for use in ambient temperatures between 5° - 35° C and all properties listed above assume a temperature of 20°C. Where conditions outside this range are encountered, please consult our technical staff prior to application.

Over application can cause staining and surface retardation. Avoid over spray onto adjacent areas.

**Material Safety Data Sheets (MSDS) are available to users of Aitken Freeman products on request. Please ensure you have read this data sheet, the MSDS, and the product label carefully before first use of any product.**

### TECHNICAL SUPPORT

Aitken Freeman offers a comprehensive range of high quality, high performance construction products. In addition, Aitken Freeman offers technical support to users and specifiers, and can arrange on-site visits to end users and contractors.

## ALLIED PRODUCTS

Aitken Freeman manufactures a broad range of construction products and can supply the following:

- Grouts and anchoring systems
- Epoxy Surface Coatings
- Admixtures for concrete
- Adhesives & Sealants
- Floor toppings
- Floor levelling compounds
- Concrete Repair materials
- Waterproofing solutions

***Refer to Material Safety Data Sheet for precautions and personal protection***

**Disclaimer:** Any advice, recommendation, information, assistance or service provided by Aitken Freeman Pty Ltd in relation to goods manufactured or supplied by them or their use and application is in good faith and is believed by Aitken Freeman Pty Ltd to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Aitken Freeman Pty Ltd is provided without liability.