



# Resiloc Thinners

## Solvent for general purpose cleaning and thinning

### USES

Resiloc Thinners is suitable for most sealers and resin based compounds, including two pack systems before they harden.

### BENEFITS

- Good Cleaning Efficiency
- Economical material
- Dries to a oil free finish
- Single pack
- Compatible with most resin systems
- Easy application by spray, roller or brush

### TECHNICAL SUPPORT

Aitken Freeman offers a comprehensive range of high quality, high performance construction products. In addition, Aitken Freeman offers technical support to users and specifiers, and can arrange on-site visits to end users and contractors.

### MIXING

Resiloc Thinners is suitable for application straight from the container without prior mixing.

### PRECAUTIONS

Resiloc Thinners is designed for use in ambient temperatures between 10° - 35° C and all properties listed above assume a temperature of 20°C. Where conditions outside this range are encountered, please consult our technical staff prior to application. Resiloc Thinners is a solvent based product, so protective goggles and clothing should be worn. Ventilation must be provided, or self-contained breathing apparatus may be appropriate. Resiloc Thinners may affect some rubber and plastic components causing them to dissolve, swell or break down over time.

## DESCRIPTION

Resiloc Thinners is a solvent designed for general purpose clean-up of equipment. Resiloc Thinners is not suitable for hardened epoxy products.

## TYPICAL PROPERTIES AND APPLICATION DATA

Appearance:	Clear liquid
Odour:	Aromatic
Solubility in Water:	Insoluble
Flash Point:	38°C
Shelf Life:	12 months
maximum	
Application Temperature:	10°C - 35°C

## APPLICATION

Add the Resiloc Thinners to the product in accordance with the manufacturer's advice.

Applications for spraying may require up to 10% Thinners.

## CLEAN UP

Resiloc Thinners may be used to clean up equipment immediately after use.

## SUPPLY

Resiloc Thinners is supplied in 20 litre or 200 litre drums

## STORAGE

Resiloc Thinners should be stored in a cool, dry place in original unopened containers. Shelf life under these conditions is 12 months

Do not store Resiloc Thinners or diluted products in plastic containers that are not compatible, or not suitable for solvent based products. Check the suitability of using Resiloc Thinners prior to commencing the application.

**Material Safety Data Sheets (MSDS) are available to users of Aitken Freeman products on request. Please ensure you have read this data sheet, the MSDS, and the product label carefully before first use of any product.**

## **ALLIED PRODUCTS**

Aitken Freeman manufactures a broad range of construction products and can supply the following:

- Grouts and anchoring systems
- Epoxy Surface Coatings
- Admixtures for concrete
- Adhesives & Sealants
- Floor toppings
- Floor levelling compounds
- Concrete Repair materials
- Waterproofing solutions

### ***Refer to Material Safety Data Sheet for precautions and personal protection***

**Disclaimer:** Any advice, recommendation, information, assistance or service provided by Aitken Freeman P/L in relation to goods manufactured or supplied by them or their use and application is in good faith and is believed by Aitken Freeman P/L to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Aitken Freeman P/L is provided without liability.

### **Location:**

Factory 7  
7 – 9 Brough St  
Springvale.Vic.3171  
Ph: 03 9701 3955  
[www.aitkenfreeman.com](http://www.aitkenfreeman.com)