

Eco Form Release Oil



Release Agent for Timber & Steel Formwork

USES

Eco Form Release Oil is a light oil based release agent for formwork for concrete, which is free of Solvents and aromatic carcinogens.

BENEFITS

- Exceptionally Low odour
- Economical – good coverage
- Ease of application
- Improves concrete surface finish
- Ready to use from container

TECHNICAL SUPPORT

Aitken Freeman offers a comprehensive range of high quality, high performance construction products. In addition, Aitken Freeman offers technical support to users and specifiers, and can arrange on-site visits to end users and contractors.

APPLICATION

Preparation

The areas to be treated with Form Release Oil must be free of oil, grease or other contaminants.

Priming

Priming is not required for this product.

Mixing

Eco Form Release Oil is supplied ready to use from the container. Do not add solvent, diesel or other oils.

ESTIMATING & SUPPLY

Eco Form Release Oil is supplied in 20,200 & 1000 litre drums. Coverage on sealed forms or steel will be 30m² per litre. New timber formwork will require a minimum of 2 coats at a coverage of 15 - 20m² per litre.

DESCRIPTION

Eco Form Release Oil is light oil based release agent that contains reactive components to ensure a clean and even concrete finish.

TYPICAL PROPERTIES

Colour	Clear liquid,
Specific Gravity	< 1.0 gm/ml

Installation

Spray application will ensure a light and even film of Eco Form Release Oil. Apply two even coats to new timber formwork. Application should be several hours prior to pouring concrete. Rain affected formwork may need an additional coat.

CLEAN UP

All spray equipment should be cleaned thoroughly before and after application to avoid contamination.

STORAGE

Eco Form Release Oil should be stored in a cool, dry place in original unopened containers. Shelf life under these conditions is 12 months.

PRECAUTIONS

Eco Form Release Oil is designed for use in ambient temperatures between 5° - 35° C and all properties listed above assume a temperature of 20°C.

Where conditions outside this range are encountered, please consult our technical staff prior to application.

Over application can cause staining and surface retardation. Avoid over spray onto adjacent areas.

ALLIED PRODUCTS

Aitken Freeman manufactures a broad range of construction products and can supply the following:

- Grouts and anchoring systems
- Epoxy Surface Coatings
- Admixtures for concrete
- Adhesives & Sealants
- Floor toppings
- Floor levelling compounds
- Concrete Repair materials
- Waterproofing solutions

Material Safety Data Sheets (MSDS) are available to users of Aitken Freeman products on request. Please ensure you have read this data sheet, the MSDS, and the product label carefully before first use of any product.

Refer to Material Safety Data Sheet for precautions and personal protection

Disclaimer: Any advice, recommendation, information, assistance or service provided by Aitken Freeman P/L in relation to goods manufactured or supplied by them or their use and application is in good faith and is believed by Aitken Freeman P/L to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Aitken Freeman P/L is provided without liability.

Locations:

Vic

Factory 7
7 – 9 Brough St
Springvale.Vic.3171
Ph: 03 9701 3955

WA

6B Chalkley Place
Bayswater.WA.6053
Ph. 1300 816 711

Website

www.aitkenfreeman.com