


# Form Release Cream



## Economical Form Release Cream

### Uses

Form Release Cream is a ready to use, non-drip form release cream which is used in application to steel hinges or vertical forms where a non-drip and long lasting release agent is required.

### BENEFITS

- Prevents concrete penetration into steel hinges and rust staining.
- Prevents distortion
- Resists transfer of splinters – forms into concrete.
- Resists exposure to weather conditions for several days prior to a concrete pour.

### Application

Form Release Cream is supplied ready to use and should be applied liberally to forms prior to use. It can be applied up to a maximum of 2 days prior to pouring.

The drying time is typically 6-8 hours depending on environmental conditions. All surplus Form Release Cream should be removed before pouring concrete.

Form Release Cream can be applied by brush, mop or glove.

### PRECAUTIONS

### DESCRIPTION

Form Release Cream is a specially formulated, non-drip form release agent, which penetrates deep into new untreated formwork, prevents distortion of forms and resists transfer of splinters into concrete from sawn forms.

The Form Release Cream reacts with the free lime in the concrete to produce a film. The film allows trapped air or free water to escape during vibration to minimise surface voids.

### SAFETY

Gloves and goggles must be worn during application.

### CLEAN UP

Form Release Cream can be cleaned using diesel.

### PACKAGING

Form Release Cream is supplied in 20 litre drums.

### COVERAGE

Approx. 8m<sup>2</sup> per litre.

Note: Coverage rate is dependent on the porosity of the form being used. The coverage rate and the form release properties will be reduced if the formwork is of an old/worn nature.

### STORAGE

Shelf life is at least 6 months, if protected from frost or prolonged exposure to elevated temperatures. Store below 30°C and above 5°C.

Form Release Cream is designed for use in ambient temperatures between 5° - 35° C and all properties listed above assume a temperature of 20°C. Where conditions outside this range are encountered, please consult our technical staff prior to application.

**Material Safety Data Sheets (MSDS) are available to users of Aitken Freeman products on request. Please ensure you have read this data sheet, the MSDS, and the product label carefully before first use of any product.**

Locations:

**Vic**

Factory 7  
7 – 9 Brough St  
Springvale.Vic.3171  
Ph: 03 9701 3955

**WA**

6B Chalkley Place  
Bayswater.WA.6053  
Ph. 1300 816 711

**Website**

[www.aitkenfreeman.com](http://www.aitkenfreeman.com)

## **ALLIED PRODUCTS**

Aitken Freeman manufactures a broad range of construction products and can supply the following:

- Grouts and anchoring systems
- Epoxy Surface Coatings
- Admixtures for concrete
- Adhesives & Sealants
- Floor toppings
- Floor levelling compounds
- Concrete Repair materials
- Waterproofing solutions

***Refer to Material Safety Data Sheet for precautions and personal protection***

**Disclaimer:** Any advice, recommendation, information, assistance or service provided by Aitken Freeman P/L in relation to goods manufactured or supplied by them or their use and application is in good faith and is believed by Aitken Freeman P/L to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Aitken Freeman P/L is provided without liability.