


Pavecure P



High Quality Polymer Emulsion Curing Compound

USES

Pavecure P is suitable for use on all freshly laid concrete either smooth or textured, indoors or outdoors. Pavecure P will help to reduce moisture loss due to evaporation from the surface of concrete.

BENEFITS

- Economical means of curing concrete
- Contains no wax - dries clear
- Single coat - easy application
- Water based material – safe and equipment can be washed in water
- Contains fugitive dye – so that you can easily see whether areas have been covered evenly

TECHNICAL SUPPORT

Through our experienced sales team, Aitken Freeman can offer technical support to users and specifiers and can arrange on-site visits to end users and contractors.

SUPPLY

Pavecure P is available in either 20 litre or 200 litre drums.

PRECAUTIONS

Pavecure P is designed for use in ambient temperatures between 5° - 40° C and all properties listed above assume a temperature of 20°C. Where conditions outside this range are encountered, please consult our technical staff prior to application.

TYPICAL PROPERTIES AND APPLICATION DATA

Appearance:	Milky homogenous liquid with green fugitive dye
Coverage:	5m ² per litre
Dry Time:	Tack Free: 1 - 3 hours
	Hard Dry: 4 - 8 hours
	Trafficable: 24 hours
Application Temperature:	10°C - 35°C
Application By:	- Spray - Brush - Roller - Broom
UN Number:	Not applicable
Hazchem Code:	Not applicable
Packaging Group:	Not applicable
Poison Schedule:	Not scheduled
Dangerous Goods Class:	Not applicable

INSTALLATION

Apply Pavecure P to the concrete as soon as the bleed water has gone, and the new concrete has hardened sufficiently so as not to be marked by the application process. Apply Pavecure P undiluted at a rate of 1 litre per 5 m².

Best applied by spray, however, may also be applied by brush, roller or broom.

STORAGE

Pavecure P should be stored in a cool, dry place in original unopened containers. Shelf life under these conditions is 12 months.

Material Safety Data Sheets (MSDS) are available to users of Aitken Freeman products on request. Please ensure you have read this data sheet, the MSDS, and the product label carefully before first use of any product.

Locations:

Vic

Factory 7
7 – 9 Brough St
Springvale.Vic.3171
Ph: 03 9701 3955

WA

6B Chalkley Place
Bayswater.WA.6053
Ph. 1300 816 711

Website

www.aitkenfreeman.com

ALLIED PRODUCTS

Aitken Freeman manufactures a broad range of construction products and can supply the following:

- Grouts and anchoring systems
- Epoxy Surface Coatings
- Admixtures for concrete
- Adhesives & Sealants
- Floor toppings
- Floor levelling compounds
- Concrete Repair materials
- Waterproofing solutions

Refer to Material Safety Data Sheet for precautions and personal protection

Disclaimer: Any advice, recommendation, information, assistance or service provided by Aitken Freeman P/L in relation to goods manufactured or supplied by them or their use and application is in good faith and is believed by Aitken Freeman P/L to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Aitken Freeman P/L is provided without liability.