


# Silax



## Impregnating Water Repellent Sealer

### USES

Silax is suitable for use on all concrete and masonry.

### BENEFITS

- Dries to a clear, invisible finish
- Single pack
- Reduces water absorption
- Can be applied by spray, roller or brush
- Will not yellow in sunlight
- Seals concrete surfaces
- Takes most after trades

### TECHNICAL SUPPORT

Aitken Freeman offers a comprehensive range of high quality, high performance construction products. In addition, Aitken Freeman offers technical support to users and specifiers, and can arrange on-site visits to end users and contractors.

### PRECAUTIONS

Avoid application to damp surfaces or on days when rain is expected. Silax is fully cured in 24 hours and will resist rain after 18 hours.

Silax cannot be applied over other impervious finishes or non-porous substrates.

Avoid overspray on adjacent glass or aluminium. Clean up overspray immediately to avoid permanent marking of the surface.

### SUPPLY

Silax is supplied in 20 litre drums.

### DESCRIPTION

Silax is a single pack siloxane, impregnating and water repellent sealer for blockwork, renders and concrete.

### TYPICAL PROPERTIES AND APPLICATION DATA

Appearance:	Clear low viscosity liquid
Coverage:	5m <sup>2</sup> per litre on block 6 – 8 m <sup>2</sup> per litre on concrete
Solubility in Water:	Insoluble
Flash Point:	36°C
Shelf Life:	12 months
Dry Time:	Touch Dry 1 - 2 hours Cured 24 hours

Application Temperature: 10°C – 35°C

Application By: - Spray- Brush- Roller -Broom

### SURFACE APPLICATION

Ensure the surface is dry before applying the Silax. Mask off adjacent areas, particularly glass and aluminium.

Apply Silax undiluted at a rate of 1 litre per 5m<sup>2</sup>. Best applied by spray, however, Silax may also be applied by brush or roller.

Apply a second coat after 18 hours to ensure an even coverage.

### STORAGE

Silax should be stored in a cool, dry place in original unopened containers. Shelf life under these conditions is 12 months.

**Material Safety Data Sheets (MSDS) are available to users of Aitken Freeman products on request. Please ensure you have read this data sheet, the MSDS, and the product label carefully before first use of any product.**

**Locations:**

**Vic**

Factory 7  
7 – 9 Brough St  
Springvale.Vic.3171  
Ph: 03 9701 3955

**WA**

6B Chalkley Place  
Bayswater.WA.6053  
Ph. 1300 816 711

**Website**

[www.aitkenfreeman.com](http://www.aitkenfreeman.com)

**ALLIED PRODUCTS**

Aitken Freeman manufactures a broad range of construction products and can supply the following:

- Grouts and anchoring systems
- Epoxy Surface Coatings
- Admixtures for concrete
- Adhesives & Sealants
- Floor toppings
- Floor levelling compounds
- Concrete Repair materials
- Waterproofing solutions

***Refer to Material Safety Data Sheet for precautions and personal protection***

**Disclaimer:** Any advice, recommendation, information, assistance or service provided by Aitken Freeman P/L in relation to goods manufactured or supplied by them or their use and application is in good faith and is believed by Aitken Freeman P/L to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Aitken Freeman P/L is provided without liability.